

Part # MICH3510S | MIC3510S | MIC3510SB



UNIVERSAL[®]
SECURITY INSTRUMENTS, INC.
ALWAYS WORKING TO
PROTECT YOUR FAMILY[®]



SHORT PRODUCT DESCRIPTION

10 Year Tamper Proof Permanent Power Sealed Battery 3-in-1 Smoke + Fire + Carbon Monoxide Smart Alarm

LONG PRODUCT DESCRIPTION

3-in-1 Alarm Protects Against Smoke + Fire + Carbon Monoxide with Universal Smoke Sensing Technology[®] Provides the benefits of both photoelectric and ionization technology + CO in one alarm. No batteries to change—ever!

FEATURES & BENEFITS

- Tamper proof design provides a higher level of security to prevent battery removal
- Gives a decade of peace of mind
- Maintenance Free Battery Power—No batteries to replace for the life of the alarm
- Saves money—Never replace batteries for 10 years, saving up to \$38.00 over the life of the alarm
- Eliminates annoying low battery chirps
- 10 year sealed batteries provide continuous protection—even in the event of a power outage
- 3-in-1 alarm protects against 3 deadly household hazards: Smoke + Fire + Carbon Monoxide
- Patented Universal Smoke Sensing Technology provides the benefits of **both** Photoelectric and Ionization technology in one alarm
- Smart Alarm Technology virtually eliminates nuisance alarms. Ideal for installation in EVERY room
- Deactivation key switches alarm off and makes alarm safe for disposal
- Lock-out feature prevents deactivated alarm from being reinstalled
- Choose this alarm if you are looking for an alarm with superior nuisance alarm resistance
- 10 year product end-of-service life warning sounds when it is time to replace alarm
- This alarm is suitable for installation in houses, apartments, dormitory and manufactured housing
- Meet New Laws & Legislation-This alarm exceeds industry standards, and ETL listed to UL Standard UL 217 and UL 2034 and California State Fire Marshal approved.
- ECO Friendly—Reduces environmental waste & eliminates disposal of up to **twenty** 9 volt batteries
- Fast & easy to install. No wiring required. Perfect for new or replacement installations
- Automatic temperature and humidity compensation continuously adjusts to variations in environmental conditions, reducing nuisance alarms
- For added security, tamper-resistant locking feature prevents unwanted alarm removal
- The larger mounting base covers drywall imperfections and old paint marks
- The single silence/test button temporarily quiets nonemergency alarms and tests alarm functionality
- Temperature Range is 40°F to 100°F (0°C to 38°C). Humidity Range is 5% to 85% relative humidity (RH)
- 10 year limited warranty on both battery and alarm

CORPORATE OFFICES

11407-A Cronhill Drive | Owings Mills, MD 21117-6218 USA
phone 410.363.3000 | fax 410.363.2218
www.UniversalSecurity.com