

Ionization, Carbon Monoxide & Natural Gas Alarm

120 Volt AC Hardwired with Battery Backup

Model MICN109



NEW 3-in-1 Smart Alarm uses a single sensor to detect both CO & Natural Gas. Microprocessor Intelligence provides superior nuisance alarm resistance, temperature & humidity compensation, self diagnostics and Quick Find[®] alarm origination features. Perfect for new or replacement installations, this hardwired 120 Volt AC/DC combination smoke and fire, carbon monoxide and natural gas alarm offers time-saving installation features, value and quality.

Features

Benefits

Advanced smoke recognition	<i>Provides faster response to smoldering fires than conventional smoke alarms</i>
Auto sensitivity calibration	<i>Prevents nuisance alarms and provides consistency</i>
Self-diagnostic feature	<i>Performs a status check upon power up to ensure alarm is functioning properly</i>
Ambient condition compensation	<i>Automatically adjusts sensitivity for temperature and humidity conditions</i>
Replacement or retrofit	<i>Any existing USI Electric or Universal brand 120V alarm using existing wiring and mounting bracket</i>
Quick activation pull tab	<i>Preserve battery life. Preinstalled battery is quickly activated without removing alarm from bracket</i>
Universal mounting bracket	<i>Fits any standard wiring junction box, single gang, round or octagon, up to 4"</i>
Quick connect wiring harness	<i>Longer 8" pigtail wires are pre-stripped</i>
Larger mounting base	<i>Covers drywall imperfections and old paint marks</i>
Quick Find [®] alarm origination feature	<i>Patented feature easily identifies first alarm to sound in an interconnected system</i>
Product end-of-service life warning	<i>Alarm signals when it is time to replace after approximately 7 years (from the date of initial power-up)</i>
Front-load battery drawer	<i>Replace battery without removing alarm from bracket</i>
Single silence/test button	<i>Temporarily quiets nonemergency alarms and tests alarm functionality</i>
Full-size plastic dust cover	<i>Protects alarm from dust, debris and painting during construction or home remodeling</i>
2 tamper resistant locking features	<i>Prevents alarm and battery removal</i>

Technical Specifications

Sensor Type:	Smoke & Fire - M Series Ionization, CO & NG - Solid State, Metal Oxide
Power:	120 Volt AC 60 Hz + 9 Volt Energizer alkaline battery backup (battery incl.)
Audible Alarm:	85 dB at 10 feet
Temperature Range:	32° F to 100° F (0° C to 38° C)
Humidity Range:	10% to 95% RH
LED:	3 LED's: alarm, power, CO, gas
Size:	5.0" x 5.0" x 2.0"
Warranty:	5 year limited

Regulatory Compliance:

California State Fire Marshal (CSFM)
 National Fire Protection Association (NFPA)
 Housing and Urban Development (HUD)
 Federal Housing Authority (FHA)
 UTGT / UTHA / CZHF (UL)



MODEL	BRAND	Box Clam	QTY	SHELF PACK (in.) L x W x H	WEIGHT (Lbs.)	UPC CODE	QTY	MASTER CTN (in.) L x W x H	WEIGHT (Lbs.)	I2 of 5
MICN109	USI	Box	1	5.50 x 5.50 x 1.75	0.72	0-42741-00109-0	6	12.13 x 6.13 x 6.00	4.8	1-00-42741-00109-7